Product datasheet

Specifications



Thorsman 18W LED - worklight UK plug 110V

Local distributor code: 401546794 IMT33098

Discontinued on: 14 December 2021

To be discontinued

Main

Range	Thorsman
Product name	Thorsman 18 LED
Product or component type	Work lamp
Light source	42 x SMD LED 5630 18 W

Complementary

Type of installation	Indoor Outdoor
[Ue] rated operational voltage	110 V
Network type	AC
Network frequency	50/60 Hz
Plug pole configuration	2P + E
Plug standard	UK
Luminous flux	1500 lm
Bulb lifespan	50000 h
Colour rendering index	Ra=80
Beam angle	100 °
Cable insulation material	Neoprene
Material	ABS (acrylonitrile butadiene-styrene) TPE (thermoplastic elastomer)
Electrical connection	Power cord H05RN-F2x1.0 2 m
Electrical insulation class	Class II
Height	200 mm
Width	200 mm
Depth	80 mm
Net weight	1.03 kg
Targeted country	UK

Environment

Environmental characteristic	Dustproof

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	Splashproof
IP degree of protection	IP54
IK degree of protection	IK07
Quality labels	CE
Ambient air temperature for operation	-25…40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.03 kg
Package 1 Height	20 cm
Package 1 width	8 cm
Package 1 Length	20 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	1
Package 2 Weight	1.2 kg
Package 2 Height	21 cm
Package 2 width	11 cm
Package 2 Length	25.5 cm
Unit Type of Package 3	PAL
Number of Units in Package 3	128
Package 3 Weight	183.6 kg
Package 3 Height	108 cm
Package 3 width	100 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months