

# Product datasheet

Specifications



## Ultimate Low profile - switched socket - 2 gangs - chrome

Local distributor code: 391286795    GU3520WBC

### Main

Aesthetic name	Low profile
Product or component type	Switched socket
Rated current	13 A at 230 V AC 50 Hz
Fixing mode	By screws M3.5 x 30 mm
Colour tint	Chrome

### Complementary

Device presentation	Complete product
Outlet poles configuration	1P
Outlet standard description	3 pins
Outlet standard	British
Actuator	Rocker
Number of gangs	2 gangs
Earth circuit	Standard earth
Pilot light	Without neon indicator
Device mounting	Wall mounted
Connections - terminals	Screw terminal
Material	Steel
Quantity per set	Set of 1
Height	88 mm
Width	148 mm
Depth	30 mm

### Environment

IP degree of protection	IP20
Standards	BS 1363

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Weight	267.0 g
Package 1 Height	15.5 cm
Package 1 width	3.9 cm
Package 1 Length	10.1 cm
Unit Type of Package 2	P12
Number of Units in Package 2	1000
Package 2 Weight	278.2 kg
Package 2 Height	115 cm
Package 2 width	100 cm
Package 2 Length	120 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Weight	13.91 kg
Package 3 Height	17.5 cm
Package 3 width	44.2 cm
Package 3 Length	52.5 cm

Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------