

Product datasheet

Specifications



Ultimate Slimline - switched fused connection - white

Local distributor code: 382626021 GU5013

Main

Range	Ultimate
Device application	Protection
Aesthetic name	Slimline
Product or component type	Switched fused connection
Switch function	Switch
Colour tint	White

Complementary

Pilot light	without neon indicator
Number of gangs	1 gang
Material	Urea (carbamide)
Mounting support	Wall mounted
Fixing mode	By screws
Rated current	13 A at 230 V AC
Connections - terminals	Screw terminals
Quantity per set	Set of 10
Height	86 mm
Width	86 mm
Depth	26 mm
Fuse type	Blade type

Environment

IP degree of protection	IP20
Standards	BS 1363

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	140 g
Package 1 Height	3.2 cm

Package 1 width	8.6 cm
Package 1 Length	8.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.458 kg
Package 2 Height	9.6 cm
Package 2 width	15.6 cm
Package 2 Length	18.6 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Weight	15.21 kg
Package 3 Height	18 cm
Package 3 width	39.3 cm
Package 3 Length	49.5 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
----------	-----------