

Product datasheet

Specifications



Ultimate Slimline dimmer switch 250W/VA, 3gang, 2way, main & LV, white

Local distributor code: 400082482 GU6032C

Main

Range of product	Ultimate
Range	Ultimate
Aesthetic name	Slimline
Product or component type	Dimmer
Device application	Control
Load type	Incandescent lamp: 250 W 230 V AC halogen lamp
Colour tint	White matt
Quantity per set	Set of 1

Complementary

Switch function	2-way
Device mounting	Wall mounted
Dimmer application	Inductive load Resistive load
[Ue] rated operational voltage	230 V AC 50 Hz
Number of gangs	3 gangs
Connections - terminals	Screw terminals
Fixing mode	By screw M3.5 x 25 mm
Material	Urea (carbamide)
Height	86 mm
Width	146 mm
Depth	35 mm

Environment

Standards	BS EN 60669-2-1
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Weight	244.0 g
Package 1 Height	4.6 cm
Package 1 width	9.2 cm
Package 1 Length	15.5 cm
Unit Type of Package 2	PAM
Number of Units in Package 2	1000
Package 2 Weight	277.6 kg
Package 2 Height	106.5 cm
Package 2 width	100 cm
Package 2 Length	120 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Weight	12.88 kg
Package 3 Height	18 cm
Package 3 width	49 cm
Package 3 Length	50 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------