

Switch disconnector

Distribution

Complementary

Device application

Product or component type

Main Range

[le] rated operational current	125 A at 415 V AC
Poles description	2P
Product destination	Distribution board
Suitable for cable cross section	50 mm ²

Environment

Standards BS EN 60947-3	
-------------------------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	167.0 g
Package 1 Height	3.5 cm
Package 1 width	7.4 cm
Package 1 Length	9 cm
Unit Type of Package 2	P06
Number of Units in Package 2	528
Package 2 Weight	106.784 kg
Package 2 Height	75 cm
Package 2 width	80 cm
Package 2 Length	60 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	6
Package 3 Weight	1.055 kg
Package 3 Height	8.5 cm

Package 3 width	9.7 cm
Package 3 Length	21.8 cm
Offer Sustainability	
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------