

SAFETY DATA SHEET
(MARK VITOW) LEAK DETECTOR SPRAY

Page: 1
Compilation date: 31/01/2019
Revision date: 02.11.22
Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: (MARK VITOW) LEAK DETECTOR SPRAY

Product code: LEAK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Aerosol leak detector.

1.3. Details of the supplier of the safety data sheet

Company name: MARK VITOW LTD

1 Silver Court

Watchmead

Welwyn Garden City

Hertfordshire

AL7 1LT

Tel: 0208 207 3784

Email: info@markvitow.com

1.4. Emergency telephone number

Emergency tel: 0208 207 3784

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; -: H229

Most important adverse effects: Pressurised container: May burst if heated. Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H229: Pressurised container: May burst if heated.

H319: Causes serious eye irritation.

Hazard pictograms: GHS07: Exclamation mark



Signal words: Warning

[cont...]

SAFETY DATA SHEET
(MARK VITOW) LEAK DETECTOR SPRAY

Page: 2

Precautionary statements: P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P260: Do not breathe vapours.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Haz. ingredients (label): Contains:
COCONUT DIETHANOLAMIDE

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

COCONUT DIETHANOLAMIDE - REACH registered number(s): 01-2119490100-53-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
931-329-6	68155-07-7	-	Skin Irrit. 2: H315; Eye Dam. 1: H318; Aquatic Chronic 2: H411	1-10%

AMMONIA SOLUTION

215-647-6	1336-21-6	-	Skin Corr. 1B: H314; Aquatic Acute 1: H400	<1%
-----------	-----------	---	--	-----

Non-classified ingredients:

WATER

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	7732-18-5	-	-	>90%

TRIETHANOLAMINE - REACH registered number(s): 01-2119486482-31-XXXX

203-049-8	102-71-6	-	-	<1%
-----------	----------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

[cont...]

SAFETY DATA SHEET
(MARK VITOW) LEAK DETECTOR SPRAY

Page: 3

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to fresh air in case of accidental inhalation of vapours.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. Aerosol cans may explode during a fire, giving a high speed projectile.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Cover leaking can until the discharge has stopped, before attempting cleanup operations.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

[cont...]

SAFETY DATA SHEET
(MARK VITOW) LEAK DETECTOR SPRAY

Page: 4

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Non-classified ingredients:

TRIETHANOLAMINE

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3 (no std.)	-	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Ensure eye bath is to hand. Safety glasses.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

[cont...]

SAFETY DATA SHEET
(MARK VITOW) LEAK DETECTOR SPRAY

Page: 5

9.1. Information on basic physical and chemical properties

State: Aerosol	
Colour: Colourless	
Odour: Characteristic odour	
Evaporation rate: Slow	
Solubility in water: Highly soluble	
Viscosity: Viscous	
Boiling point/range°C: 100	Melting point/range°C: Not applicable.
Flammability limits %: lower: Not applicable.	upper: Not applicable.
Flash point°C: Not applicable.	Part.coeff. n-octanol/water: No data available.
Autoflammability°C: Not applicable.	Vapour pressure: Not applicable.
Relative density: Not applicable.	pH: 8.5 - 9.5
VOC g/l: Not applicable.	

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Direct sunlight. Hot surfaces. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

[cont...]

SAFETY DATA SHEET
(MARK VITOW) LEAK DETECTOR SPRAY

Page: 6

Hazardous ingredients:

COCONUT DIETHANOLAMIDE

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	5000	mg/kg

AMMONIA SOLUTION...100%

IVN	MUS	LD50	91	mg/kg
ORL	RAT	LD50	350	mg/kg
SCU	MUS	LDLO	160	mg/kg

Non-classified ingredients:

TRIETHANOLAMINE

ORL	RAT	LD50	>2	g/kg
SKN	RBT	LD50	>10	g/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

COCONUT DIETHANOLAMIDE

FISH	96H LC50	2.4	mg/l
------	----------	-----	------

[cont...]

SAFETY DATA SHEET
(MARK VITOW) LEAK DETECTOR SPRAY

Page: 7

TRIETHANOLAMINE

FISH	48H EC50	1390	mg/l
FISH	96H LC50	>5000	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable. The surfactant(s) contained in this preparation complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Volatile. Readily absorbed into soil. Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Recycling/reclamation of metals and metal compounds.

Waste code number: 16 05 05

Disposal of packaging: Dispose of as normal industrial waste. Empty cans must not be burned because of explosion hazard.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

[cont...]

SAFETY DATA SHEET
(MARK VITOW) LEAK DETECTOR SPRAY

Page: 8

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

All substances in this preparation are registered within UK/EU/EFTA countries under the REACH (UK/EC) (amended) regulations, EC 1907/2006

IMPORTANT NOTE:

Risk phrases in this section below relate to the INDIVIDUAL COMPONENTS in the formulation when used at their FULL CONCENTRATIONS, and not at the reduced levels in the mixed product.

See sections 2 and 3 for the calculated hazard and risk phrases for the blended product.

Phrases used in s.2 and s.3: H229: Pressurised container: May burst if heated.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.